

# STAR<sup>®</sup>

## LITHIUM SYSTEM-2BA415



A lithium-ion or Li-ion battery is a type of rechargeable battery that uses the reversible intercalation of Li+ions into electronically conducting solids.

### GENERAL

- Nominal Voltage: 48V
- Working Voltage: 40.5V-54.75V
- Recommended Voltage: 45.0V-52.5V
- Cells: 30
- Nominal Capacity: 210 Ah
- Energy: 10,080 Wh
- Reserve @ 25A: 252 Minutes
- Self Discharge: 3% per month
- IP Rating: IP65

### DISCHARGING

- Max Continuous Discharge: 350A
- Max Discharge 20 sec: 480A
- Max Discharge 3 sec: 700A
- Recom Voltage Cutoff: 45.0V
- BMS Voltage Cutoff: 40.5V
- BMS Voltage Recovery: 45.0V
- Discharge Temp Range: 4°F~140°F

### PHYSICAL

- Cell Chemistry: Lithium Iron Phosphate
- Cell Type: Prismatic
- Cell Configuration: 2P15S
- Weight: 1981 lbs (90Kg)
- Dimension: 21" L x 18" W x 9.8" H
- Terminal Type: M8 Female
- Shell Type: Powder Coated Steel
- UN Shipping Class: UN 3480

### CHARGING

- Recom. Charging Current: 25A
- Max Charging Current: 40A
- BMS High Voltage Cutoff: 54.75V
- Charging Temp. Range: 32°F ~ 131°F

### SAFETY

- Charging Freeze Protection: Under 32° F
- Pack Over-Voltage: Yes
- Pack Under-Voltage: Yes
- Cell Under-Voltage: Yes
- Cell Over-Temp: Yes
- BMS Over-Temp: Yes
- Short Circuit / Over Current
- Certifications: UN38.3, UL1642 Cell

### COMMUNICATION

- Bluetooth
- CAN
- WIFI

